

RRT-135D / RRT-135ES (Electric Start)



FMTTI Approved

Engine Model	SR186FAD 4 Stroke Diesel Engine
Rated Output/ Rotary Speed (Kw/r/min)	6.2 kw / 3000
Bore & Stroke (mm)	86 x 72
Displacement	418cc
Fuel Tank Capacity (L)	5.5
Driving Mode	Gear Transmission
Gear	2,1,0,-1
Rotor Speed With Engine At 3600 (r/min)	Fast: 128, Slow: 64, Reverse: 48
No. Gear speed	2F+1R
Air Cleaner	Oil bath type
Tilling Depth (cm)	≥ 10
Tilling Width (cm)	135
Blades Type	5-4 / 40pcs
Tire Type	4.00 - 8
Gross Weight (kg)	160
Optional Accessories	Cage wheel, water pump, deep tillage blades & Plough

Inter Cultivation Equipment

Ralli ROTARY TILLER with Diesel engine is equipped with four stroke 418 cc Diesel Engine with recoil starter & PTO shaft for power transmission from the engine to the gearbox. Sturdy carbon steel blades for tilling purpose, adjustable handle bars for up-down & 360 degree adjustments. Rain forced blade guard, provided gearbox with forward, first, second & reverse gear system for power transmission. Transportation wheel is provided.

Ralli Brush Cutter

BC-430S



FMTTI Approved

Specifications

Aluminium Pipe Dia	Pipe Length	Blade length	Fuel Tank Capacity	Engine Power	Max Output
28mm	1500 mm	255mm	1.0 ltr	1.7 HP	1.25 kw/ 7000r/min

- Ideal for cutting fresh or dry grass on ground, lawn, fields and also for cutting small bushes, bamboos, sugarcane etc. with accessories
- Light weight & very powerful brush cutter
- Straight solid shaft & heavy duty gear case
- Anti-vibration design that reduces operator's fatigue
- Durable, efficient & labour saving cutting equipment
- Air cooled, 2 stroke 43 cc Engine

Brush Cutters

Ralli BRUSH CUTTER is an ideal partner for cutting the weeds. Ralli BRUSH CUTTER is being preferred by the farmers as the most durable, efficient, & labour saving cutting equipment, which can be used for agriculture purpose. Ralli BRUSH CUTTER is designed for use under the least favorable conditions..