

Ralli EARTH AUGER

Model : **RALLI EAD**



Specifications		RALLI EAD
Engine	Standard	Double Operation
	Type	Forced air cooled, 2 stroke, single cylinder
	Displacement	63.3
	Max. Output (kw/r/min)	2.2kW/7500r/min
	Carburetor Type	Diaphragm Type
	Oil Capacity	2 stroke luboil (L-EQ)
	Oil Capacity	30:1 Gasoline and oil mixing ratio 30:1
	Ignition System	CDI (Capacitor discharge ignition)
	Starting System	Recoil and hand -operated
Shaft	Reduction ratio	1:37
	Idle Speed (r/min)	2800±150
	Clutch speed (r/min)	4000±300
	Drill diameter (mm)	Standard: 200
		Optional: 80/100/150/200/250/300
	Digging Specifications (Hang Drive mm x Pit depth mm)	200x600 (Use standard drill)
	Net Weight(kg)	10.4

Ralli Agrotech Ltd.

An ISO 9001:2015 Certified Company

Regd. Office :

Poddar HMP House, 4, Fairlie Place,
Kolkata - 700001, Ph: +91 81000 80353,
E-mail: info@ralliagri.com
CIN: U51909WB1995PLC076016

Works : Plot No 278 & 279, N.H. 8, Village-Nandawala, Taluk & District-Valsad,
Pin-396001, Gujarat, India

Sales Network :

Ahmedabad, Bangalore, Baroda, Bhopal, Chennai, Coimbatore, Cuttack, Delhi,
Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur,
Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam



Follow us :



www.ralliagri.com

+91 90734 93011