

# Ralli Horizontal Triplex Piston Pump (HTP)

## RTP - 70



### Specifications

Suction Capacity (lpm)	70
Normal Working Pressure	100 - 200 psi
Max. Pressure	500 psi
Pump Revolution	950
Power (hp) - Prime Mover	5 HP
L X W X H (in mm)	340 X 300 X 295
Weight (without oil)	15 kg (approx)

- Suitable for large spraying operations in Orchards, Coffee, ground crops etc.
- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting Rod
- Control valve assly. With pressure regulator, by-pass
- Pulsation free spray

Ralli RTP-70 HTP horizontal triplex power sprayer unit, developing 500 PSI (35 Bar) pressure, supplied with pulley, glycerin filled pressure gauge, by pass cum pressure regulator valve, by-pass hose & suction hose with strainer.

## Ralli Engine Operated HTP Sprayer Set

### RS65 - 22 / RS65 - 30



### Specifications

Engine Type	4 stroke single cylinder Petrol Engine
Displacement	196CC
Power	6.5HP
Engine RPM Maximum	3600 rpm
Maximum Pressure	2 to 3 mpa (or) 10 to 40 Bar
Suction and Discharge	20 - 22 ltr/min / 30 ltr/min
Fuel Tank	3 Liter
Engine Oil Capacity	600 ml
Pump Oil Capacity	600 ml;
Pump RPM	800 - 1200 rpm
Starting System	Recoil Starter

- Suitable for large spraying operations in orchards, coffee & tea plantations and ground crop etc.
- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting rod