

Ralli GASOLINE CHAIN SAW



Specifications		RALLI D50E
Engine	Type	2 STROKE
		Forced air cooled, 2 stroke, single cylinder
	Displacement	50.8cc
	Max. Output (kw/r/min)	2.2kw/9000r/min
	Max torque (N·m/r/min)	2.65/6500
	Operating Noise Level (7m) dB(A)	104dB(A)
	Fuel consumption (g/kW.h)	< 540
	Oil/Fuel Tank Capacity (L)	0.28L/0.54L
	Chain oil	SAE#10W-30
	Fuel oil	FC 2 stroke gasoline engine oil
	Mix rate	30:1 Gasoline and oil mixing ratio 30:1
	Ignition System	CDI (Capacitor discharge ignition)
	Starting System	Recoil and hand -operated
	Vibration level (m/s ²)	Front handle: 5.5 ; Rear handle: 5.8
	Chain (pitch×gauge)	.325×.058
Weight	Bar length	16" 18" 20"
	Net Weight	5.8kg

Ralli Agrotech Ltd.

An ISO 9001:2008 Certified Company

www.ralliagri.com

REGISTERED OFFICE : Poddar HMP House, 4, Fairlie Place, Kolkata - 700001,
Ph: +91 81000 80353, Fax: +91 33 2243 6966, E-mail: info@ralliagri.com
CIN: U51909WB1995PLC076016

WORKS : Plot No 278 & 279, N.H. 8, Village-Nandawala, Taluk & District-Valsad,
Pin-396001, Gujrat, India

SALES NETWORK : Ahmedabad, Akola, Ambala, Bangalore, Bhubaneswar, Bhopal,
Chennai, Coimbatore, Delhi, Guwahati, Jaipur, Kolkata, Ludhiana, Mumbai, Nagpur,
Pune, Raipur, Secunderabad, Trichy, Vijaywada



**PODDAR
HMP GROUP**