

Ralli EARTH AUGER

RALLI EAS



Specifications		RALLI EAS
Engine	Standard	Single operation
	Type	Forced air cooled, 2 stroke, single cylinder
	Displacement	51.7
	Max. Output (kw/r/min)	1.3kW/7000r/min
	Carburetor Type	Diaphragm Type
	Oil Capacity	2 stroke luboil (L-EQ)
	Oil Capacity	30:1 Gasoline and oil mixing ratio 30:1
	Ignition System	CDI (Capacitor discharge ignition)
	Starting System	Recoil and hand -operated
Shaft	Reduction ratio	1:37
	Idle Speed (r/min)	2800±280
	Clutch speed (r/min)	4200±350
	Drill diameter (mm)	Standard: 100
		Optional: 80/100/150
	Digging Specifications (Hang Drive mm× Pit depth mm)	100×600 (Use standard drill)
	Net Weight(kg)	9,5

Ralli Agrotech Ltd.

An ISO 9001:2008 Certified Company

www.ralliagri.com

REGISTERED OFFICE : Poddar HMP House, 4, Fairlie Place, Kolkata - 700001,
Ph: +91 81000 80353, Fax: +91 33 2243 6966, E-mail: info@ralliagri.com
CIN: U51909WB1995PLC076016

WORKS : Plot No 278 & 279, N.H. 8, Village-Nandawala, Taluk & District-Valsad,
Pin-396001, Gujrat, India

SALES NETWORK : Ahmedabad, Akola, Ambala, Bangalore, Bhubaneswar, Bhopal,
Chennai, Coimbatore, Delhi, Guwahati, Jaipur, Kolkata, Ludhiana, Mumbai, Nagpur,
Pune, Raipur, Secunderabad, Trichy, Vijaywada



**PODDAR
HMP GROUP**