

Ralli High Pressure Knapsack Sprayer - (Premium Range, 4 stroke)

ultramax



FMTTI Approved

Specifications

Chemical Tank Capacity	Spraying Capacity	Speed Range	Engine	Weight
20 Ltr.	3-5.5 Ltr./min	3000-6500 rpm	GX-25 HONDA	12kg (approx)

- Suitable for different crops application
- 20 Lt. capacity corrosion resistant HDPE tank with adjustable nylon straps assembly
- Supplied with 25.0 cc 4 stroke GX-25 Honda engine
- Engine produces high torque for better field operation
- Diaphragm type carburetor is equipped with accelerator pump for fast, easy acceleration
- Light weight & compact construction
- The sprayer is equipped with auto agitation system

POWERED by
HONDA
ENGINE

Ralli High Pressure Knapsack Sprayer (Fitted with Japanese Carburetor)

920 - 2S



Specifications

Chemical Tank Capacity	Working Pressure	Engine	Speed Range	Spraying Capacity
20 Litres	200-300 psi	2 stroke, 26cc	3000-6500 rpm	3-8 L/min

- Suitable for different crops application
- 20 Lt. capacity corrosion resistant HDPE tank with adjustable nylon straps assembly
- Supplied with 26cc 2 stroke Engine
- Pressure develops up to 400 psi
- Ideal for all type of field crops and horticultural crops
- Engine fitted with recoil starter for easy starting
- Spray lance & spray gun supplied with sprayer
- Highly mobile single S.S. Piston pump developing maximum 400 psi
- Light weight & compact construction

Plant Protection Equipment