

Ralli Manual Cum Battery Operated Sprayer

Ralli 21



Two Variants - 12V 8.0 AMP
- 12V 12.0 AMP

TTCFM Junagadh Approved

Specifications

Chemical Tank Capacity	Working Pressure	Battery	Weight
18 Litres	80 psi	12V 8.0 AMP / 12V 12.0 AMP	4 kg (w/o Battery)

- Same Sprayer we can use as Battery operated Sprayer and Manual Sprayer
- Big Pressure chamber retain maximum pressure at the time of spraying
- Adjustable shoulder strap
- Convenient battery housing with charger point Made from PPTank
- More safety for the Operator & Environment.
- Reduction for effective spraying time cost efficient.
- Suitable for spraying in Paddy, Vegetables, Orchards and Plantations Light Weight
- S.S. Brass joint Telescopic lance with plastic cut off & plastic Nozzle
- Auto Cut-Off & Pressure regulator switch

RALLI 21 - 2 IN 1 Battery Sprayer is provided with 18 ltr capacity High Density Polyethylene tank. It is suitable for large spraying operations in orchards, coffee & plantation.

Ralli Horizontal Triplex Piston Pump (HTP)

RTP - 16 / RTP - 22A



Specifications

Suction Capacity (lpm)	16 / 20
Normal Working Pressure	100 -200 psi
Maximum Pressure	400 psi
Pump Revolution	1000 rpm
Power (hp) - Prime Mover	2
L x W x H (in mm)	275 x 270 x 265
Weight (without oil & pulley)	7 kg (approx)

- Suitable for large spraying operations in orchards, coffee & tea plantations and ground crop etc.
- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting rod

Ralli RTP-16 HTP horizontal triplex power sprayer unit, developing 400 PSI (28 Bar) pressure, supplied with pulley, glycerin filled pressure gauge, by-pass cum pressure regulator valve, by-pass hose & suction hose with strainer.