

Ralli Horizontal Triplex Piston Pump (HTP)

RTP - 30



Specifications

Suction Capacity (lpm)	30
Normal Working Pressure	100 - 200 psi
Max. Pressure	500 psi
Pump Revolution	950
Power (hp) - Prime Mover	3 ~ 4 HP
L X W X H (in mm)	340 X 300 X 295
Weight (without oil)	9 kg (approx)

- Suitable for large spraying operations in Orchards, Coffee, ground crops etc.
- Heavy duty & efficient sprayer
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting Rod
- Control valve assly. With pressure regulator, by-pass
- Pulsation free spray
- Develop pressure up to 500 psi max.
- Sturdy/Rugged

Ralli RTP-30 HTP horizontal triplex power sprayer unit, developing 500 PSI (35 Bar) pressure, supplied with pulley, glycerin filled pressure gauge, by pass cum pressure regulator valve, by- pass hose & suction hose with strainer.

Ralli Horizontal Triplex Piston Pump (HTP)

RTP - 50 / RTP - 50B (Cast Iron) (Brass)



FMTTI Approved

Specifications

Suction Capacity (lpm)	50
Normal Working Pressure	100 - 200 psi
Max. Pressure	500 psi
Pump Revolution	950
Power (hp) - Prime Mover	5 HP
L X W X H (in mm)	340 X 300 X 295
Weight (without oil)	12 kg (approx)

- Suitable for large spraying operations in Orchards, Coffee, ground crops etc.
- Sturdy/rugged construction
- Heavy duty & efficient sprayer
- Stainless steel piston
- All working parts are lubricated by oil bath
- Aluminum pressure die casting connecting Rod
- Control valve assly. With pressure regulator, by-pass
- Pulsation free spray
- Develop pressure up to 500 psi max.

Ralli RTP-50 HTP horizontal triplex power sprayer unit, developing 500 PSI (35 Bar) pressure, supplied with pulley, glycerin filled pressure gauge, by pass cum pressure regulator valve, by- pass hose & suction hose with strainer.