

## RMT60



### Specifications

Automatic Grade	Semi- Automatic
Production Capacity	Maize>1500-2000 kg/hr,
Suitable for threshing	Sun Dried Whole Maize
Power Required (hp)	Electric Motor:1Hp, Gasoline Engine:7.5Hp
Voltage	220V
Spindle Speed (rpm)	1600 rpm
Electric Consumption	0.8 Kw/h
Net Weight	24.5Kg (Without electric motor)

- Mainly used to thresh dried maize
- Good performance with less breakage of maize and cob
- Operator only put complete maize into machine
- 5TW-60 will separate maize from cob high-efficiently
- Benefit for maize farmers

## Ralli Rotary Tiller cum Power Weeder with Petrol Engine (5.3 HP)

### RRT-100P



FMTTI Approved

Engine Model	170F/P 4 Stroke Petrol Engine
Rated Output/Rotary Speed (Kw/r/min)	3.9kw / 3100
Bore & Stroke (mm)	70 x 55
Displacement	212 cc
Fuel Tank Capacity (L)	3.6
Driving Mode	Gear Transmission
Gear	2,1,0-1
Rotor Speed With Engine At 3600 (r/min)	Fast: 130, Slow: 101, Reverse: 73
No. Gear speed	2F+1R
Air Cleaner	Oil Bath Type
Tilling Depth (cm)	≥ 10
Tilling Width (cm)	100
Blades Type	4-3 / 24pcs
Tire Type	4.00 - 8
Gross Weight (kg)	102
Optional Accessories	Cage wheel, Water Pump, deep tillage blades & Plough

Ralli ROTARY TILLER with petrol engine is equipped with four stroke 212 cc petrol Engine with recoil starter & PTO shaft for power transmission from the engine to the gearbox. Sturdy carbon steel blades for tilling purpose, adjustable handle bars for up-down adjustments. Rein forced blade guard, provided gearbox with forward, first, second & reverse gear system for power transmission .Transportation wheel is provided.