

Ideal for irrigation in multicrop applications Small size, compact structure, easy to move.

Lingine Type	4 Stroke sirigle diyrider i etror Erigirie
Displacement	196CC
Power	6.5HP
Engine RPM Maximum	3600 rpm
Maximum Pressure	2 to 3 mpa (or) 10 to 40 Bar
Suction and Discharge	20 - 22 ltr/min
Engine Tank	3 Liter
Engine Oil Capacity	600 ml
Pump Oil Capacity	600 ml;
Pump RPM	800 - 1200 rpm
Starting System	Recoil Starter

Ralli Agrotech Ltd.

An ISO 9001:2015 Certified Company

Regd. Office:

4, Fairlie Place, Kolkata - 700001, Phone: +91 96749 17311 E-mail: info@ralliagri.com, Website: www.ralliagri.com

Works: Plot No 278 & 279, N.H. 8, Village-Nandawala, Taluk & District-Valsad, Pin-396001, Gujarat, India

Sales Network:

Ahmedabad, Akola, Bangalore, Baroda, Bhopal, Bhubaneswar, Chennai, Coimbatore, Cuttack, Delhi, Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur, Patna, Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam, Vijayawada

















